

# Stratasys J55

The Stratasys J55™ 3D printer combines the quality of Stratasys PolyJet technology with a compact, office-friendly design.

The five material channel, full color printer features a rotating build platform with fixed print head for outstanding surface finish and print quality. Engineered for the office or design studio environment, it features a small footprint and ProAero™ filtration technology for odor free, silent and low power operation.

The J55 offers a streamlined design-to-print workflow powered by GrabCAD Print™. This allows users to import their designs using native CAD files or 3MF file formats. GrabCAD Print also enables Pantone® validated color matching\*. Remote monitoring lets you easily manage your print jobs from outside the office. Additionally, hands-free soluble support removal makes post processing simple and enables the creation of complex parts without compromising accuracy or detail.

## Product Specifications

Model Materials	<input checked="" type="checkbox"/> VeroCyanV™ <input checked="" type="checkbox"/> VeroMagentaV™ <input checked="" type="checkbox"/> VeroYellowV™ <input type="checkbox"/> VeroPureWhite™ <input checked="" type="checkbox"/> VeroBlackPlus™	<input type="checkbox"/> VeroClear™ <input checked="" type="checkbox"/> DraftGrey™ <input type="checkbox"/> VeroUltra™ WhiteS <input checked="" type="checkbox"/> VeroUltra™ BlackS <input type="checkbox"/> VeroUltra™ ClearS
Support Materials	SUP710™	
Build Size/Printing Area	140 x 200 x 187 mm (5.51 x 7.87 x 7.48 in.) 1,174cm <sup>2</sup>	
Layer Thickness	Horizontal build layers down to 18 microns (0.0007 in.)	
Network Connectivity	LAN - TCP/IP	
System Size and Weight	651 x 661 x 1511mm (25.63 x 26.02 x 59.49 in.); 228 kg (503 lbs.)	
Operating Conditions	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)	
Power Requirements	100-240VAC, 50-60 HZ, 10A, 1 phase	
Regulatory Compliance	CE, FCC, EAC, cTUVus, CB, RCM	
Software	GrabCAD Print	
Build Modes	High Quality Speed (HQS) – 18.75µm	
Accuracy	Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – ±150µ; above 100 mm – ±0.15% of part length.**  Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm – ±180µ; above 100 mm – ±0.2% of part length.**	

\*PANTONE Validation in process.

\*\*Measured when ambient temperature is 23 °C and relative humidity is 50%.

### Stratasys Headquarters

7665 Commerce Way,  
Eden Prairie, MN 55344  
+1 800 801 6491 (US Toll Free)  
+1 952 937-3000 (Intl)  
+1 952 937-0070 (Fax)

1 Holtzman St., Science Park,  
PO Box 2496  
Rehovot 76124, Israel  
+972 74 745 4000  
+972 74 745 5000 (Fax)

[stratasys.com](http://stratasys.com)

ISO 9001:2015 Certified

